

BOQ

BOQ

Sub-Repair of aluminum enclosure

S. No	DSR Ref	Description of Items	Qty	Unit	Rate	Amount
1	9.55	Providing and fixing ISI marked M.S. pressed butt hinges bright finished with necessary screws etc. Complete :				
	9.55.1	125x65x2.12 mm	12.00	Nos		
2	9.81	Providing and fixing bright finished brass handles with screws etc. complete:				
	9.81.1	125 mm	4.00	each		
3	9.96	Providing and fixing aluminium sliding door bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with nuts and screws etc. Complete :				
	9.96.1	300x16 mm	2.00	each		
4	9.97	Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. Complete :				
	9.97.3	200x10 mm	4.00	each		
5	9.101	Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.				
	9.101.2	Twin rubber stopper	4.00	each		
6	21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS : 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer in charge. (Glazing and paneling to be paid for separately) :				
	21.1.1.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	60.00	kg		
	21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/pivots and making provision for fixing of fittings wherever required including the cost of PVC / neoprene gasket required (Fittings shall be paid for separately).				
	21.1.2.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	25.00	kg		
7	NS	Providing and fixing ACP sheet 5mm thick single side laminated with neoprene gasket and silicon sealant complete in all respect to the direction of Engineer in Charge.	7.50	sqm		
8	NS	Repair of door by dismantling the same, repair and refix the same including replacing the EPDM neoprene rubber.	16.00	Nos		
9	NS	P/f of EPDM rubber gasket	50.00	mtr		
10	NS	Uprooting of old jali and fixing of new jali with MS frame	4.50	sqm		
		Total				

Contractor