BOQ

Name of Work: P/f of partition in Hostel at IISER Mohali.

Sr. No./ DSR	Description of Item	Qty	Unit	Rate	Amount
1/ 9.71	Providing and fixing IS: 12817 marked stainless steel butt hinges (heavy weight) with stainless steel screws etc. complete:				
9.71.1	125 x 64 x 2.50mm	8	no.		
2/ 9.76	Providing and fixing bright finished brass 100mm mortice latch ans lock with 6 levers and a pair of lever handles of approved quality with necessary screws etc. complete.	1	nos.		
3/ 9.83	Providing and fixing IS : 3564 marked Aluminium die cast body tubular type universal hydraulic door closer with necessary accessories and screws etc. Complete.	1	each		
4/ 9.97	Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete :				
9.97.4	150x10 mm	2	each		
5/ 9.100	Providing and fixing Aaluminium handles, ISI marked, anodised (anodic coated not less than grade AC 10 as per ISI : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete.				
9.100.1	125mm	2	nos.		
	Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.				
9.101.2	Twin rubber stopper	1	each		
7/ 0 125	Providing and fixing fly proof tainless steel garde 304 wire gauge, to windows and clerestory windows using wire guage with average width of aperture 1.4mm in both directions with wire of dia. 0.50 mm all complete.				
				i	1

8/ 21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS : 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing and paneling to be paid for separately) :			
21.1.1.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	82	kg	
21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of PVC / neoprene gasket required (Fittings shall be paid for separately).	22	kg	
9/ 21.2	Providing and fixing 12mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.			
21.2.2	Pre-laminated particle board with decorative lamination on both sides.	13	sqm	
	TOTAL			

Contractor