

Name of Work: P/f of Partition in HRMS at IISER Mohali.

Sr. No./ DSR	Description of Item	Qty	Unit	Rate	Amount
1/ 9.71	Providing and fixing IS: 12817 marked stainless steel butt hinges (heavy weight) with stainless steel screws etc. complete:				
9.71.1	125 x 64 x 2.50mm	8	no.		
2/9.76	Providing and fixing bright finished brass 100mm mortice latch and lock with 6 levers and a pair of lever handles of approved quality with necessary screws etc. complete.	1	nos.		
3/9.83	Providing and fixing IS : 3564 marked Aluminium die cast body tubular type universal hydraulic door closer with necessary accessories and screws etc. Complete.	1	nos.		
4/ 9.96	Providing and fixing aluminium sliding door bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with nuts and screws etc. complete :				
9.96.1	300x16 mm	2	each		
5/ 9.100	Providing and fixing aluminium handles , ISI marked, anodised (anodic coated not less than grade AC 10 as per ISI : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete.				
9.100.1	125mm	4	nos.		
6/ 21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS : 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing and paneling to be paid for separately) :				
21.1.1.2	For fixed portion				
21.1.1.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	450	kg		
21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of PVC / neoprene gasket required (Fittings shall be paid for separately).				
21.1.2.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	50	kg		
7/ 21.3	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with PVC/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item) :				
21.3.2	With float glass panes of 5.50 mm thickness	20.00	sqm		
8/NS	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with pvc/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (cost of aluminium snap beading shall be paid in basic item).	65.00	sqm		
	TOTAL				

Contractor