

BOQ

| S.No. | Description of item | Qty | Unit | Rate | Amount |
|----------|---|-----|------|------|--------|
| 1/11.36 | Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. | 5 | sqm | | |
| 2/ 11.41 | Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3kg/sqm including grouting the joints with white cement and matching pigments etc., complete. | | | | |
| 11.41.2 | Size of Tile 600x600 mm | 60 | sqm | | |
| 3/13.1 | 12 mm cement plaster of mix : | | | | |
| 13.1.2 | 1:4 (1 cement: 4 fine sand) | 10 | sqm | | |
| | Total | | | | |

Contractor