

Sheet3

BOQ

Sub: Covering of LPG cylinders on the terrace of AB1 at IISER Mohali

Sno/ DSR 2014	Description	Qty	Unit	Rate	Amount
1/ 4.1	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :				
4.1.3	1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size	0.50	cum		
2/ 10.26	Providing and fixing hand rail of approved size by welding etc. to steel ladder railing, balcony railing and staircase railing including applying a priming coat of approved steel primer.				
10.26.1	M.S. tube.	200.00	kg		
3/ 13.61	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :				
13.61.1	Two or more coats on new work	22.00	sqm		
4/ 15.7	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.				
15.7.4	In cement mortar	0.50	cum		
5/ NS	P/f of 6mm polycarbonate muyltiwall white/coloured sheet including aluminum beading and rubber all complete as per direction of Engineer in Charge.	22.00	sqm		
	Total				