

## BOQ

SUB: PARTITION IN THE VISUAL ROOM IN THE INFORMATICS BUILDING AT IISER MOHALI

SR.NO	DSR	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
1	9.76	Providing and fixing bright finished brass 100 mm mortice latch and lock with 6 levers and a pair of lever handles of approved quality with necessary screws etc. complete.	4	no		
2	9.83	Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete.	4	no		
3	9.97	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868 ) transparent or dyed to required colour or shade, with necessary screws etc. complete :	8	no		
	9.97.3	200*10mm				
4	9.100.1	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :	8	no		
5	9.101	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :				
	9.101.2	twin rubber stopper	4	no		
6	21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber / neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				

	21.1.1A	for fixed portion				
	21.1.1.1	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	8	kg		
	21.1.1.2	Powder coated aluminium coating 50 micron minimum thickness of powder	315	kg		
	21.1.2 B	For shutters of doors, windows & ventilators including providing and fixing hinges / pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)	82	kg		
7	N.S	providing fixing ACP sheet having thickness 3mm, PVDF coating, whether rsistance, impact resistance etc. inluding / PVC ETC.(aluminum composite sheet,in panelling fixed in aluminum doors , windows shutters and partition frames with steel screws rtc complete as per dawings and direction ofengineer-in-charge.	45.5	sqm		
		Total				

Contractor