

BOQ

BOQ

Sub- Preparation of femtosecond laser lab

S. No	DSR Ref	Description of Items	Qty	Unit	Rate	Amount
1	NS	P/f of 0.5 micron Hepa filter of size 300x300mm made of aluminum frame having efficiency of 80% and above	4.00	nos		
2	NS	P/f of exhaust fan having dia of 300mm, ISI marked heavy duty including power wiring	4.00	Nos		
3	NS	P/f of fibre sheet having thickness 5mm over the aluminum frame of approved make and manufacturer as directed by Engineer-in-Charge	75.00	sqm		
4	NS	Sliding roller for making sliding arrangement of aluminum doors	8.00	nos		
5	9.75	Providing and fixing bright finished brass door latch with necessary screws etc. complete :				
	9.75.1	300x16x5 mm	4	Nos		
6	9.97	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :				
	9.97.1	300x10 mm	8	Nos		
7	9.100	Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. Complete :				
	9.100.1	125 mm	16	Nos		
8	9.103	Providing and fixing bright finished brass 100 mm mortice latch and lock, ISI marked, with six levers and a pair of anodised (anodic coating not less than grade AC 10 as per IS : 1868) aluminium lever handles of approved quality with necessary screws etc. complete.	8	Nos		
9	21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS : 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing and paneling to be paid for separately) :				
	21.1.1.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	160.00	kg		
10	21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)				
	21.1.2.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	150.00	Kg		
		Total				

Contractor