

BOQ

Sub: Covering of windows and open area with ACP sheet

Sr. No.	Discription of Items	Qty	Unit	Rate	Amount
N.S	P/f of 3mm PVDF ACP sheet in walls & ceilings with screws to seal it proper all complete as per direction of Engineer-in-charge.	45	sqm		
NS	P/f of 3mm PVDF ACP sheet in partitions with neoprene all complete as per direction of Engineer-in-charge.	3	sqm		
NS	Sliding roller for making sliding arrangement of aluminum doors	1.00	nos		
9.97	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :				
9.97.1	300x10 mm	1	Nos		
9.100	Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. Complete :				
9.100.1	125 mm	2	Nos		
9.103	Providing and fixing bright finished brass 100 mm mortice latch and lock, ISI marked, with six levers and a pair of anodised (anodic coating not less than grade AC 10 as per IS : 1868) aluminium lever handles of approved quality with necessary screws etc. complete.	1	Nos		
21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				
21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of PVC / neoprene gasket required (Fittings shall be paid for separately).				
21.1.2.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	35.00	kg		
	Total				

Contractor