

## BOQ

Sub: Repair work in restaurant at IISER, Mohali

Sr. No.	DSR 2014	Description of Items	Qty	Unit	Rate	Amount
1	4.1	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :				
	4.1.8	1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	1.5	Cum		
2	6.4	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :				
	6.4.1	Cement mortar 1:4 (1 cement : 4 coarse sand)	0.7	Cum		
3	9.62	Providing and fixing ISI marked oxidised M.S. sliding door bolts with nuts and screws etc. complete :				
	9.62.2	250x16 mm	1	Each		
4	9.63	Providing and fixing ISI marked oxidised M.S. tower bolt black finish, (Barrel type) with necessary screws etc. complete :				
	9.63.1	250x10 mm	1	Each		
5	11.26	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) :				
	11.26.1	25 mm thick	16	Sqm		
6	11.36	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete	3.86	Sqm		
7	13.45	Finishing walls with textured exterior paint of required shade :				
	13.45.1	New work (Two or more coats applied @ 3.28 ltr/10 sqm) over and including priming coat of exterior primer applied @ 2.20kg/10 sqm	22	Sqm		
8	13.80	Providing and applying white cement based putty of average thickness 1mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	22	Sqm		
9	21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing)				
	21.1.2.1	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	40	Kg		
10	NS	Repair of toughned glass door.	1	Nos		
11	NS	Providing and fixing ACP sheet having thickness 5mm, PVDF coating, whether resistance, impact resistance etc including neuprene/PVC gasket etc the directions of	2.92	Sqm		
12	NS	Repair of aluminium Door	2	Nos		
13	NS	Taps	2	Nos		
		Total				

Contractor