

BOQ

Sub: C/o Platform

Sr.No.	Description of Item	Qty.	Unit	Rate	Amount
1/2.6	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means over areas (exceeding 30cm in depth, 1.5m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m, disposed earth to be levelled and neatly dressed.				
2.6.1	All kinds of soil	10	cum		
3/2.25	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.	8.00	cum		
4/2.27	Supply and filing in plinth with jamuna sand under floors including watering, ramming, consolidating and dressing all complete	5.00	cum		
5/4.1	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :				
4.1.10	1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size)	4.00	cum		
6/4.12	Extra for providing and mixing water proofing material in cement concrete work @ 1 kg per 50kg of cement.	50.00	Per 50 kg cement bag		
7/4.17	Making plinth protection 50mm thick of cement concrete 1:3:6 (1 cement :3 coarse sand : 6graded stone aggregate 20mm nominal size) over 75mm bed by dry brick ballast 40mm nominal size well rammed and consolidated and grouted with fine sand including finishing the top smooth	25.00	sqm		
8/5.1	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level :				
5.1.2	1:1.5:3 (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size)	15.00	cum		
9/5.9	Centering and shuttering including strutting, propping etc. and removal of form for :				
5.9.3	Suspended floors, roofs, landings, balconies and access platform.	15	sqm		
10/5.22	Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete.				
5.22.6	Thermo-Mechanically Treated bars.	2300	kg		
11/6.1	Brick work with F.P.S. bricks of class designation 75 in foundation and plinth in:				
6.1.2	Cement mortar 1:6 (1 cement : 6 coarse sand)	5	cum		
12/6.44	Brick edging 7cm wide 11.4cm. deep to plinth protection with bricks of class designation 75 including grouting with cement mortar 1:4 (1 cement : 4 fine sand)	30	mtr.		
13/13.4	12 mm cement plaster of mix :				
13.4.1	1:4 (1 cement: 4 coarse sand)	50	sqm		
14/20.2	Boring, providing and installing bored cast-in-situ reinforced cement concrete pile of specified diameter and length below the pile cap M 35 in cement concrete, to carry a safe working load not less than specified, excluding the cost of steel reinforcement but including the cost of boring with, bentonite solution and temporary casing of appropriate length for setting out and removal of same and the length of the pile to be embedded in the pile cap etc. all complete, including removal of excavated earth with all lifts and leads (Length of pile for payment shall be measured upto bottom of pile cap).				
20.2.1	300 mm dia piles	72	mtr		
	Total				

Contractor