

BOQ

Sub: Closing of open enclosure along the railing in Informatics centre at IISER, Mohali

Sr. No.	Discription of Items	Qty	Unit	Rate	Amount
1	P/f of 10mm thick toughened glass including joining the glass pieces with 3M tape at all height as per the Direction of Engineer-in-Charge	90	sqm		
2	P/f of 75 MM bottom channel section, 2mm thick made up of anodised with sand blasted aluminum section to be used for supporting the glass at the bottom including fixing to the existing vitrified tile flooring . (section as per enclosed drawing and specifications HSM 75.02+HSM75.08)	40	rmt		
3	P/f of 75 X 18MM top channel channel section, 2mm thick made up of anodised with sand blasted aluminum section to be used for supporting the glass at the top by dismanteling the existing gypsum board ceiling and repairing the same i. (section as per enclosed drawing and specificationstop section to be used for HSM 75.06 + HSM 75.07)	85	rmt		
4	P/f of floor spring FS-8400 Make DORMA/OZONE	1	No		
5	P/f of handle OGH 55 35*457	2	Nos		
6	P/f of OPL 1 corner plate lock with strike plate	1	No		
7	P/f of OPF 1 over panel side panel connecting patch with pivot	1	No		
	Total				

Contractor