

BOQ

Sr. No.	DSR 2014	Description of Items	Qty	Unit	Rate	Amount
1	6.4	Brick work with F.P.S. bricks of class designation 75 in foundation and plinth in:				
	6.4.1	Cement mortar 1:4 (1 cement : 4 coarse sand)	5.5	cum		
2	11.26	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) :				
	11.26.1	25 mm thick	12	sqm		
3	13.1	12 mm cement plaster on the rough side of single or half brick wall of mix :				
	13.1.1	1:4 (1 cement: 4 fine sand)	45.00	Sqm		
4	13.45	Finishing walls with textured exterior paint of required shade :				
	13.45.1	New work (Two or more coats applied @ 3.28 ltr/10 sqm) over and including base coat of water proofing cement paint applied @ 2.20kg/10 sqm.	45.00	sqm		
5	16.84	Labour for carriage of paver stones from lead upto 100 mtr and fixing the same over 50mm sand all complete as per direction of Engineer-in-charge.	10.00	sqm		
6	NS	Providing and laying 60mm thick factory made cement concrete interlocking prepolished rubber moulded paver block of M -35 grade made by block making machine with strong vibratory compaction and of approved size and design/ shape laid in required colour and pattern over and including 20-30mm thick compacted bed of coarse sand, filling the joints with fine sand etc. all complete as per the direction of Engineer-in-charge.	2	sqm		
		Total				

Contractor