

BOQ

Sr. No.	Description of Items	Qty	Unit	Rate	Amount
1/ 9.74	Providing and fixing bright finished brass tower bolts (barrel type) with necessary screws etc. complete :				
9.74.3	150x10 mm	2.00	each		
2/ 9.76	Providing and fixing bright finished brass 100 mm mortice latch and lock with 6 levers and a pair of lever handles with necessary screws etc. complete (best make of approved quality).	1.00	each		
3/ 9.83	Providing and fixing IS : 3564 marked Aluminium die cast body tubular type universal hydraulic door closer with necessary accessories and screws etc. complete.	2.00	each		
4/ 9.101	Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.				
9.101.2	Twin rubber stopper	2.00	each		
5/ NS	P/f of 5mm PVDF ACP sheet single side lamination in partitions with neoprene all complete as per direction of Engineer-in-charge.	7	sqm		
6/ 21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				
21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of PVC / neoprene gasket required (Fittings shall be paid for separately).				
21.1.2.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	50.00	Kg		
7/ NS	P/f of 12 mm thick toughened glass for partition and making necessary holes for the accessories, etc (accessories will be paid extra)	18.00	sqm		
8/ NS	P/f of one way spider for ceiling/wall OSP A22 of MAKE OZONE/DORMA/DLINE	10.00	Nos		
9/ NS	P/f fixed bolt (flat head) OSP FB FL of MAKE OZONE/DORMA/DLINE	1.00	Nos		
10/ NS	P/f of floor spring FS 8400 of MAKE OZONE/DORMA/DLINE	2.00	Nos		
11/ NS	P/f of over panel side panel connecting patch with pivot OPF 1 of MAKE OZONE/DORMA/DLINE	10.00	Nos		
12/ NS	P/f of glass door handle with locking function OGH 55 32*457 of MAKE OZONE/DORMA/DLINE	2.00	Nos		
13/ NS	P/f of bottom patch OPF3 of MAKE OZONE/DORMA/DLINE	6.00	Nos		
14/ NS	P/f of Glass to glass connector OGC-2 of MAKE OZONE/DORMA/DLINE	4.00	Nos		
15/ NS	Dismantling of shutter and repair on the wall all complete	1	Job		
	Total				

Contractor