

BOQ

BOQ

Name of Work: P/F of Aluminium partition in AHU room of Lecture Hall at IISER Mohali.

Sr. No./ DSR	Description of Item	Qty	Unit	Rate	Amount
1/ 9.76	Providing and fixing bright finished brass 100mm mortice latch and lock with 6 levers and a pair of lever handles of approved quality with necessary screws etc. complete.	4	nos.		
2/9.83	Providing and fixing IS : 3564 marked Aluminium die cast body tubular type universal hydraulic door closer with necessary accessories and screws etc. Complete.	4	each		
3/ 9.97.4	Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete :				
9.97.4	150x10 mm	4	each		
4/ 9.100	Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete :				
9.100.1	125 mm	8	each		
5/ 9.101	door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.				
9.101.2	Twin rubber stopper	4	each		
6/ 21.1	windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS : 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing and paneling to be paid for separately) :				
21.1.1.1	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	230	kg		

BOQ

21.1.2.1	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	55	kg		
7/ 21.2	Providing and fixing 12mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.				
21.2.2	Pre-laminated particle board with decorative lamination on both sides.	65	sqm		
8/NS	P/f of door seal with necessary screws etc. in aluminum door all complete as per the Engineer-in-charge.	4	each		
	TOTAL				

Contractor

BOQ

BOQ